

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:

(11) International Publication Number:

WO 87/05536

B03C 1/00, 1/28, G01N 33/553

A1 |

(43) International Publication Date:

24 September 1987 (24.09.87)

(21) International Application Number:

PCT/SE87/00120

(22) International Filing Date:

11 March 1987 (11.03.87)

(31) Priority Application Number:

8601143-3

(32) Priority Date:

12 March 1986 (12.03.86)

(33) Priority Country:

SE

(71) Applicant (for all designated States except US): CAR-BOMATRIX AB [SE/SE]; Ferievägen 9, S-223 67 Lund (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SCHRÖDER, Ulf [SE/SE]; Ferievägen 9, S-223 67 Lund (SE).

(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö (SE).

(81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), DK, FI, FR (European patent), GB (European patent), HU, IT (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent), SU, US.


Published

With international search report. In English translation (filed in Swedish).

(54) Title: METHOD AND APPARATUS FOR COLLECTING AND DISPERSING FERROMAGNETIC PARTI-CLES IN A FLUID MEDIUM

(57) Abstract

A method and apparatus for collecting ferromagnetic particles in a gaseous or liquid medium, and dispersing them in a gaseous or liquid medium, in which method a magnet is introduced into said medium. Use is made of a sleeve (5) of a plastic material permeable to the magnetic field, but free of remanence and having a thin-walled nose end (6) and a thick-walled jacket wall. Mounted in the passageway (7) of the sleeve is a permanent magnet body (10) of the type which, when attached to an operating means (11, 13), is movable within said passageway in the longitudinal direction thereof by means of said operating means from the open sleeve end, the permanent magnet being moved by means of said operating means into the closed nose end for collecting the ferromagnetic particles (3). To disperse the particles, the permanent magnet is moved to a position spaced from the nose.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	·Mali
ΑŪ	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark	MC	Monaco	US	United States of America

MG Madagascar

Finland

10

15

25

30

METHOD AND APPARATUS FOR COLLECTING AND DISPERSING FERROMAGNETIC PARTICLES IN A FLUID MEDIUM

The present invention relates to a method and an apparatus for collecting and dispersing ferromagnetic particles in a fluid medium.

US-3,985,649 discloses a process for separating a substance from a liquid in a container utilising magnetic forces. The substance is formed of ferromagnetic particles which are actuated, for the said separation, by means of an electromagnet immersed in the liquid. The ferromagnetic particles may have been formed of a ferromagnetic core and a reaction product bonded thereto, optionally via a coating, and formed of a first reactant bonded to the core or the coating prior to the introduction of the cores into the liquid, and a second reactant within the liquid. For the said actuation of the ferromagnetic particles, the electromagnet is energised and then attracts the particles and can be removed from the liquid and the container together with the particles.

The ferromagnetic particles thus removed from

the liquid and the reaction product which may be bonded
thereto, can be subjected to further processing steps
in other liquids, in which case the electromagnet
may be deenergised.

One disadvantage of this technique is that, after the electromagnet has been deenergised, a multitude of the ferromagnetic particles are retained by the electromagnet due to residual magnetism (remanence). If, for example, the separated particles are to be analysed in respect of reaction yield, the analysis will be inaccurate. The alternative of removing this particle quantity from the electromagnet takes a fairly long time, and this is also the case if the electromagnet is to be cleaned for reuse in a new environment

10

15

20

25

30

35

Š

that must not be contaminated by residual particles originating from a previous use of the electromagnet for the purpose in question.

Furthermore, the electrical lead-ins of the electromagnet constitute an obstacle to easy and convenient handling of the magnet.

It is the object of this invention to eliminate these shortcomings.

This object is achieved by means of a method and an apparatus which has the characteristic features stated in the claims.

The thin-walled, nose-shaped end of the plastic sleeve which is permeable in respect of magnetism but free of remanence, causes the ferromagnetic particles to collect around this end when the permanent magnet is inserted therein, the shoulder interconnecting the nose and the relatively thick jacket wall preventing said particles from following, on the outer side of said jacket wall, the movement of the magnet when displaced from the nose in order to disperse the particles.

The sleeve preferably is an inexpensive massproduced single-service plastic product for collecting and dispersing the ferromagnetic particles.

The invention will now be described in more detail, reference being had to the accompanying drawing illustrating an uncomplicated basic embodiment of an apparatus for carrying the method according to the invention into effect. A test tube 1 contains a liquid 2 with ferromagnetic particles 3. An apparatus according to the invention, or a probe, for collecting and dispersing these particles is designated 4. It comprises a cylindrical, for example injection-moulded plastic sleeve 5 having a closed nose-shaped end 6. The sleeve 5 has a passageway 7 which is of uniform width and extends from the open end 8 of the sleeve into the nose 6. The nose 6 thus has a thinner jacket

25

30

wall than the body 9 of the sleeve, and also a thin end wall. The passageway 7 accommodates a permanent magnet 10 for reciprocal movement within the passageway 7 in the longitudinal direction thereof by means of a shank 11 attached to said magnet in some suitable manner and extending through the open end 8. To effect the reciprocal movement, a coiled spring 12 may be positioned between a flange 13 on the shank and a flange 14 on the sleeve.

The plastic material for the sleeve is so selected that it is permeable to the magnetic field of the magnet 10 at the thin nose wall, but less permeable to this field via the thicker body wall 9. The plastic material has minimum residual magnetism (remanence), if any at all.

When the probe 4 is inserted in the tube 1 and the magnet 10 is moved into the nose 6, the spring 12 being compressed between the flanges 13 and 14 which are held between the fingers of one hand, the ferromagnetic particles 3 will collect on and adhere to the nose. When the magnet is moved in the opposite direction, which may be achieved by easing the finger pressure on the flange 13, the particles 3 are released from the sleeve 5. They cannot accompany the magnet 10 in its upward movement because of the shoulder between the nose 6 and the jacket wall 9 of the body. In this manner, magnetic particles 3 to which adheres a reactant/reaction product/absorbent/adsorbent or the like originating in the liquid 2, are transferred to another test tube containing another liquid for reaction or further treatment therein, after dispersion in said other liquid.

The construction described above is a basic one.

It may be made more sophisticated in a manner obvious

to those skilled in the art by providing, for example,

means for locking the magnet 10 in the collecting

position and the releasing/dispersing position, for

WO 87/05536 PCT/SE87/00120

4

5

10

15

example by means of a mechanism resembling the mechanism of a ballpoint pen for locking the retracted and extended positions of a spring-loaded ink cartridge.

Bearing these locking means in mind, a person skilled in the art will have no difficulty in devising a mechanism to provide for rotatability of the sleeve 5 about the shank 11 and the magnet 10 by the same hand which effects longitudinal movement of the magnet 10. Such rotation may be accomplished by means of a rack and gear mechanism, a clock-winding spring, etc. The advantage of having a rotatable sleeve 5, especially if the sleeve is provided with wings, is that the liquid and the ferromagnetic particles therein can be agitated, possibly after they have been released by the sleeve 5.

15


20

CLAIMS

- 1. A method of collecting ferromagnetic particles to which is bonded a reactant/reaction product/bonding agent or the like, in a first gaseous or liquid medium, and dispersing them in a second gaseous or liquid medium, in which method use is made of a magnet for actuation of said ferromagnetic particles, c h a racterised by utilising a sleeve of plastic material permeable to the magnetic field, but free of remanence and having a thin-walled closed nose end and a thick-walled jacket wall; providing within the passageway of said sleeve a permanent magnet body of the type which, when attached to an operating means, is movable within the passageway from the open sleeve end by means of said operating means in the longitudinal direction of said passageway; moving said permanent magnet within said sleeve, with the sleeve end inserted in said first medium, into said nose end by means of said operating means, for collecting the ferromagnetic particles within said first medium; and moving said permanent magnet, with the sleeve end inserted in said second medium, from the position inserted in said nose end to a position within said sleeve spaced from said nose end, for dispersing said particles in said second medium.
- 2. A method as claimed in claim 1, c h a r a c t e r i s e d in that the ferromagnetic particles are transferred, with the magnet inserted in the nose, from a liquid in a first container to a liquid in a second container in which the particles are released by moving the magnet to a position spaced from the nose.
 - 3. An apparatus for carrying the method as claimed in any one of claims 1 and 2 into effect, c h a r a c t e r i s e d in that it comprises a cylindrical sleeve (5) of plastic material permeable to the magnetic

field, but free of remanence and having a closed nose-shaped end (6) and a passageway (7) extending from the open sleeve end into the nose, said passageway accommodating a permanent magnet (10) which is movable in the longitudinal direction of said passageway and connected to an operating means (11, 13) for the said movement.

- 4. An apparatus as claimed in claim 3, c h arac t e r i s e d in that a spring (12) is adapted to effect movement of the permanent magnet.
- 5. An apparatus as claimed in any one of claims 3 and 4, c h a r a c t e r i s e d in that said sleeve (5) is rotatable relative to said magnet (10).



INTERNATIONAL SEARCH REPORT International Application No PCT/SE87/00120

		atent Classification (IPC) or to both Na	/1		
		, 1/28, G O1 N 33/)))		
II. FIELDS	SEARCHED	Minimum Dogume	Patellan Constant 7		
Classification	on System	Maining Docum	Classification Symbols		
IPC 4	В	03 C 1/00, /02, /	28, /30; G O1 N 33/	553	
		Documentation Searched other to the Extent that such Document	than Minimum Documentation s are included in the Fields Searched *	A	
,	SE, NO, E	OK, FI classes as	above		
		DERED TO BE RELEVANT		I Batawas As Aluta No. 10	
ategory •	Citation of I	Document, 11 with Indication, where ap	propriate, of the relevant passages 12	Relevant to Claim No. 13	
X Y	US, A,	2 970 002 (SAMUEL 31 January 1961	LAVIANO)	3-5 1,2	
Y	EP, A3,	0 140 787 (INSTIT		1,2	
	&	See figures, clai FR, 2554016 JP, 60216259 OA, 7851 US, 4649116	.ms.		
E,X	WO, Al,	86/06493 (LABSYST 6 November 1986 See figure 4, cla EP, 0220255	•	1-5	
"A" doct cons "E" earli filing "L" doct which citat	sidered to be of paier document but p g date ument which may th is cited to esta- lion or other speci	ed documents: 10 general state of the art which is not articular relevance published on or after the international throw doubts on priority claim(s) or blish the publication date of another at reason (as specified) an oral disclosure, use, exhibition or	"T" later document published after or priority date and not in conficited to understand the princip invention "X" document of particular relevancement be considered novel of involve an inventive step "Y" document of particular relevancement be considered to involve document is combined with one ments, such combination being	flict with the application but ole or theory underlying the nce; the claimed invention rearnot be considered to nce; the claimed invention an inventive step when the e or more other such docu-	
	ument published p r than the priority	nor to the international filing date but date claimed	in the art. "A" document member of the same	patent family	
	FICATION Actual Complete	a of the International Parent	Base of Sauthan and the control of t		
	-05-18	on of the International Search	1987 -05- 2 5		
Internation	at Searching Auth	ority	Signature of Authorized Officer		
	ich Pate	nt Office	Ulf Nyström		